



INFiLED FLOOR SERIES – 7.8 MM

Specification Sheet

KEY FEATURES



Magnetic connection from panel-to-panel



Integrated power and data connections allow for fast, clean cabling



Durable construction allowing to hold the weight of a mid-sized SUV

OVERVIEW

Dive into innovation with the INFiLED Floor Series – 7.8mm LED display, transforming spaces into captivating visual platforms. Versatile and durable, it adapts to various settings, enhancing engagement and creativity.



SPECIFICATIONS

Pixel Pitch	7.81mm	Ave Power Consumption	100 w/ panel
Physical Density	16,384pixels/m ²	Viewing Angle	110°/110°
Module Resolution	32×32pixels	Operating Power Source	100-240V AC 50-60Hz
Module Dimension	250×250mm (9.84×9.84in)	Operating Temperature	-10°C~+45°C
LED Arrangement	3 IN 1 SMD	Refresh Rate	1,000~2,400 Hz (Configurable)
Cabinet Resolution	64×64 pixels	Protecting Rating	IP65
Cabinet Dimension	500×500×85mm (19.69×19.69×3.35in)	Max Load-bearing	2,500kg/m ² (3 times safety factor)
Cabinet Weight	16 kg (35.27lb)	Signal Input Source	Composite, S-Video, Component HDMI, SDI, HD SDI, VGA, DVI
Brightness Level	1,500~5,000 nits	Verification	EMC, ETL, LVD
Max Power Consumption	300 w/ panel		

*Notes: The specifications are for reference, actual values may vary.