



## AOTO MINI LED - 1.5MM

### Specification Sheet

#### KEY FEATURES



170° viewing angle makes it perfect for trade show activations



Mini LED pods are more resistant than standard SMDs



Ultra high contrast offers near perfect visual quality

#### OVERVIEW

Experience the pinnacle of visual technology with the Aoto Mini LED - 1.5MM display, offering unmatched clarity and precision for diverse applications. Its meticulous craftsmanship ensures seamless integration, high refresh rates, and energy efficiency, elevating content delivery to new heights, where technological brilliance meets visual artistry.



## SPECIFICATIONS

Pixel Pitch	1.5625 mm	Module Size	W: 150 mm; H: 337.5 mm
Brightness	Standard 800 nits, Max 1,000 nits	Cabinet Resolution	384(W) x 216(H) = 82,944 dots
LED Type	Mini 4 in1	Cabinet Size	W: 600mm; H: 337.5mm
Processing Depth	24 bits	Cabinet Area	0.2025 m
Display Size	27 Inch (600 mm x 337.5 mm x 60 mm )	Viewing Angle	H: 170°±5°; V: 170°±5°
Lifespan	100,000 hours	Refresh Rate	3840 Hz
IP Rating	IP30	Contrast Ratio	8000:1
Operation Environment	Temperature: -10 °C—40 °C/Humidity: 10% - 80% RH	Input Voltage	AC100 V to AC240 V; 50 or 60 Hz
Pixel Density	409,600 dots/m	Maximun Power	135 W/Cabinet
Pixel Configuration	1R 1G 1B	Cabinet Material and Color	Die-casting Aluminium, Black
Module Resolution	96(W) x 216(H) = 20,736 dots	Maintenance	Front or Rear
		Cabinet Weight	8.5 Kg

\*Notes: The specifications are for reference, actual values may vary.