




LO series

LO4.81/LO5.95/LO6.25



Features:



Brightness up to 7000nits, best performance even against direct sunlight



Smaller pixel's pitch 4.8mm let the audience enjoy the brilliant visual closer



Optional bigger size of panel 500X1000mm is quite suitable for big project, meanwhile the price is lower



Easy to build different sizes video wall with two kind of panels (500*500mm and 500*1000mm)



Half thickness than traditional panel, saving the space of installation



Full sealed module works more reliable and stable



Tools-free lock design, makes the installation easier and faster



Specifications:

Pixel Pitch(mm)	5.95
Pixel Density(dots/m ²)	28,224
LED Type	SMD 2727
Panel Size(mm)	500*1000*80
Module Size(mm)	250*250
Cabinet Pixels	84*168
Module Pixels	42*42
Panel Weight(kgs)	13
Panel Material	Die-Casting Aluminium
Maintenance Mode	Rear Maintenance
Viewing Angle(°)	H140/V140
Drive Mode	1/7
Brightness(cd/m ²)	5,500
Refresh Rate(hertz)	≥1,200
Grey scale(bits)	16
Voltage(v)	110/220(AC)
Average Power Consumption(w/m ²)	231
Max. Power Consumption(w/m ²)	640
Operating Humidity Range	10~90%
Operating Temperature Range	-20℃~65℃
Ingress Protection(front/rear)	IP65
Lifetime(h)	100,000

Remarks: All product specifications are for reference only and subject to change without prior notice; Please contact sales for details

Dimension:

(Unit:mm)

