

ALUVISION™
MODULAR EXHIBIT CONCEPTS



Hi-LED 55



Supreme image quality



Unique dimensions



Advanced all-in-one design



MATRIX
VISUAL



TECHNICAL SPECIFICATIONS



PIXEL PITCH

2.58 mm



VIEWING ANGLE

140° / 120°
(H/V)



VIEWING DISTANCE

2.5: $\geq 8.20'$



CABINET DIMENSIONS

19.53" x 19.53" x 2.17"



PIXEL DENSITY

2.5: 13,920 px/ft²



MODULE RESOLUTION

2.5: 192 x 192 px



CABINET WEIGHT

2.5: 21.66 lb



CERTIFICATION

CE/TUV/EMC/LVD/
RoHS/ETL/FCC



SENDING BOX (*)

Nova 300, 660,
660 pro



POWER BOX

2.5: Nova A8S



REFRESH RATE

3840 Hz



OPERATING SYSTEM

Windows 2000/
XP/Vista/10



CONSUMPTION

2.5: 50/152,5 W/tile



CONTRAST RATIO

2.5: 7000:1



BRIGHTNESS

1000 nits



GRAYSCALE

14 Bit

(*) Max amount of tiles to be connected to one sending box: Nova 300 has 2 data ports and controls up to 34 tiles (2.5). Nova 660 has 4 data ports, controls up to 61 tiles (2.5) and allows easy adjustment of most basic functions. Nova 660 is advised for rental use.

CONTACT

ALUVISION USA
1620 Satellite Boulevard, Suite C
Duluth, GA 30097
O: (470) 252 3500
info@aluvision.com



MATRIX
VISUAL