



UNILUMIN URM - 3.9MM

Specification Sheet

KEY FEATURES



Creative Installation



Bottom Protection



Modular Design



Compatible PSU Box

OVERVIEW

Unilumin URM - 3.9MM presents a stunning visual experience with its finely-tuned 3.9mm pixel pitch, delivering exceptional clarity and precision. Whether for corporate presentations or immersive displays, this LED panel redefines visual excellence with its advanced technology and impeccable craftsmanship.

SPECIFICATIONS

Pixel Pitch	3.9mm
Environment	Indoor & Outdoor
LED Type	3-in-1 Black SMD
Brightness	800 cd/m ²
Parameter Value	65,536 pixels/m ²
Pixel Density	250mm × 250mm
Module Size (W×H)	500mm×500mm×83mm
Panel Size (W×H×D)	500 x 500 mm & 500mm×1,000mm×83mm
Panel Resolution	500mm×1,000mm×83mm 128 x 256 dots
Panel Weight	7.9 kg 13 kg
Ingress Protection	IP30
Material	Die-cast Aluminum
Operating Temperature/Humidity	-10°C to 45°C / 10% - 80% RH
Maintenance	Rear
Curve (Convex - Concave)	-10° to 10°
Contrast Ratio	3,000:1
Refresh Rate	3,840 Hz
Input Voltage	100 - 240 VAC
Input Power Frequency	50 - 60 Hz
Standard Mounting Configuration	Hanging, Stacking

*Notes: The specifications are for reference, actual values may vary.