

Graphite

Title	GP2.6	GP3.1	GP3.9
Pixel Pitch	2,604mm	3,125mm	3,91mm
LED Configuration	SMD 1515 Black	SMD 1515 Black	SMD 1515 Black
Max Brightness Calibrated	1500nits	1500nits	1500nits
Panel Dimension	500mm x 1000mm x 80mm 19,7" x 39,4" x 3,1"	500mm x 1000mm x 80mm 19,7" x 39,4" x 3,1"	500mm x 1000mm x 80mm 19,7" x 39,4" x 3,1"
Panel Resolution (H x V)	192 x 384	160 x 320	128 x 256
Weight Per Panel	9kg 19,84lbs	9kg 19,84lbs	9kg 19,84lbs
Power Consumption Max/Average	320W / 160W	320W / 160W	320W / 160W
BTU Max/Average	1100 / 500	1100 / 500	1100 / 500
Transparency	Solid	Solid	Solid
Serviceability	Front / Rear	Front / Rear	Front / Rear
Curving (Concave & Convex)	Concave 5° - Convex 5°	Concave 5° - Convex 5°	Concave 5° - Convex 5°
Viewing Angle Vertical	140°	140°	140°
Viewing Angle Horizontal	160°	160°	160°
Refresh Rate	7680Hz	3840Hz	3840Hz
Gray Scale	16bit	14bit	14bit
Operational Temp/Humidity	-20°C ~ 45°C, 10% ~ 90% HR -4°F ~ 113°F, 10% ~ 90% HR	-20°C ~ 45°C, 10% ~ 90% HR -4°F ~ 113°F, 10% ~ 90% HR	-20°C ~ 45°C, 10% ~ 90% HR -4°F ~ 113°F, 10% ~ 90% HR
Storage Temp/Humidity	-40°C ~ 60°C, 10% ~ 90% HR -40°F ~ 140°F, 10% ~ 90% HR	-40°C ~ 60°C, 10% ~ 90% HR -40°F ~ 140°F, 10% ~ 90% HR	-40°C ~ 60°C, 10% ~ 90% HR -40°F ~ 140°F, 10% ~ 90% HR
IP Rating	Indoor	Indoor	Indoor

Certifications	CE, ETL, FCC, UKCA	CE, ETL, FCC, UKCA	CE, ETL, FCC, UKCA
Scan Ratio	1/16	1/16	1/16
Max. Hanging	12 panels	12 panels	12 panels
Max. Stacking	6 panels	6 panels	6 panels

Please note: The specifications are for reference only, actual values may vary. For the complete disclaimer, please go to <https://www.roevisual.com/disclaimer>.