



# RECIENCE – 1.5 MM

## Specification Sheet

### KEY FEATURES



Compatible with BeMatrix and Aluvision Frames



XGOB Technology – Less pixel loss during installation/dismantle



90-Degree Seamless Corners



Concave curving up to 10-degree

### OVERVIEW

Designed for perfection, these ultra-fine 1.5mm pixel pitch tiles deliver stunning visuals with remarkable detail, making them ideal for a wide range of indoor applications. Whether you're showcasing high-definition videos, immersive graphics, or dynamic presentations, Recience - 1.5 MM ensures every detail is vividly portrayed, captivating your audience like never before.



## SPECIFICATIONS

Series	RE155d	Cabinet Res (px)	320 x 320
MicroX mode (cd/m <sup>2</sup> )	>3500	System	Stacking / Hanging / Stitching
Distance	>1.55m	Drive Mode (scan)	1/40
LED kind	MicroX	Environment	IP65 / IP54
Protection	X-GOB	Max Power (w/m <sup>2</sup> )	(CCT) 600
Pixel Density (dots/m <sup>2</sup> )	416025	Voltage	AC 100-240V
Technology	MicroX	Weight (kg/Panel)	9.2
Refreshrate	1920Hz-3840Hz	Certification	CE, EMC, TUV-EMC, FCC, ETL, UL, PSE, CCC, ROHS
Viewing Angle	160°(H)/160°(V)		
Contrast Ratio	6000:1		
Module Size (mm)	248 x 248		
Cabinet Size (mm)	496 x 496 x 55 / 62		

\*Notes: The specifications are for reference, actual values may vary.